KÜHTREIBER® ///

KIT 500 W

PROCESSOR

30-450 A

430 A/60%



Code	50575	
Input power 50/60 Hz [V]	3x400	
Protection – slow [A]	32	
Welding current range [A]	30 – 450	
Output voltage range [V]	50 – 50	
Duty cycle 100 % [A]	310	
Duty cycle 60 % [A]	430	
Duty cycle 45 % [A]	450	
Mains current/input 60 % [A/kVA]	25/17.3	
Winding	Cu	
Number of adjustment points	40	
Digital volt-ampere meter	yes	
Wire feeder	4-roll	
Standard equip roll	1.0 – 1.2	
Wire feeder speed [m/min]	1 – 20	
Material of wire - Steel, Stainless steel - Aluminium - Cored wire	•	
Ingress Protection	IP 21	
Dimensions [mm]	872 × 620 × 880	
Weight [kg]	158	
FEATURES		
2-STROKE / 4-STROKE	•	
BURN BACK	•	
EASY USE	•	
PRE-GAS / POST-GAS	•	
SPOT PULS	•	
FEED BACK	•	
UP-DOWN	•	
SOFT START	•	
GENERATOR	•	
TEST GAS	•	

DESCRIPTION

KIT 500 W are professional welding machines equipped with a high-powered transformer with copper primary and secondary winding, robust all-metal wire feeder with an efficient motor, an EURO connector and electronics control.

The main advantages are excellent welding skills, 40-grade voltage control, high power, high duty cycle, high reliability and very easy operating of version PROCESSOR.

USAGE

All machines are designed for medium and heavy machinery production, maintenance plants and metal-producing.

W – The W variant includes a liquid cooling circuit for

a welding torch.